

PMMP-PC-(1+1)x1 Pump Combiner

Features


Low insertion loss
High Pump Efficiency
stability and reliability

Application:

Continuous Wave Fiber Laser
High-Power Laser Equipment
Experimental tests and other areas

Description	Parameter	Unit	Note
Type	PMMP-PC-(1+1)x1		
Direction	Backward		
Pump Wavelength	916	nm	
Signal Wavelength	1064	nm	
Pump Fiber	MM-105/125-0.22NA	μm	
Signal Fiber	10/125-0.14/0.46NA	μm	
Output Fiber	8/125-0.14/0.46NA	μm	
Signal Insertion Loss	0.5	dB	
Pump Efficiency	90	%	
M2	1.2		
PER	18	dB	
Each port Power	20	W	
Operating Temperature	-5-+70	°C	
Storage Temperature	-20-+70	°C	
Fiber Length	1	m	
Operating Humidity	5-95	%RH	
Dimensions	70*12*8	mm	

Mechanical Dimension



Ordering Information

GCPMMP-PC-(1+1)X1-1-2-3-4-5-6-7-8-9

1	Pump Propagation Direction	B - Backward F - Forward
2	Pump Wavelength	976 - 976nm Other - Specify
3	Signal Wavelength	1030 - 1030nm Other - Specify
4	Pump Fiber Type	MM-S105/125-0.22NA Other - Specify
5	Signal Fiber Type	PLMA-GDF-14/125 Other - Specify
6	Output Fiber Type	PLMA-GDF-14/125 Other - Specify
7	Each port Power	400W - 400 W power
8	Package Type	70(L) x12(W) x8(H) Other - Specify
9	Fiber Length	1 m- 1meter Other - Specify