


MPC (18+1) x1 Pump Combiner**Features**

Low insertion loss
High Pump Efficiency
stability and reliability

Application:

Continuous Wave Fiber Laser
High-Power Laser Equipment
Experimental tests and other areas

Description	Parameter	Unit	Note
Type	MPC-(18+1)x1		
Direction	Backward		
Pump Wavelength	916	nm	
Signal Wavelength	1064	nm	
Pump Fiber	MM 135/155 0.22NA	μm	
Signal Fiber	20/400 DCF 0.065/0.46NA	μm	
Output Fiber	20/250 DCF 0.075/0.46NA	μm	
Signal Insertion Loss	0.2	dB	
Pump Efficiency	96	%	
M2	-		
PER	-	dB	
Each port Power	250	W	
Operating Temperature	-5-+70	°C	
Storage Temperature	-40-+85	°C	
Fiber Length	1.2	m	
Operating Humidity	5-95	%RH	
Dimensions	185*15*11	mm	

Mechanical Dimension**Ordering Information****GCMPC-(18+1)X1-1-2-3-4-5-6-7-8-9**

1	Pump Propagation Direction	B - Backward F - Forward
2	Pump Wavelength	976 - 976nm Other - Specify
3	Signal Wavelength	1030 - 1030nm Other - Specify
4	Pump Fiber Type	MM-S105/125-0.22NA Other - Specify
5	Signal Fiber Type	PLMA-GDF-14/125 Other - Specify
6	Output Fiber Type	PLMA-GDF-14/125 Other - Specify
7	Each port Power	400W - 400 W power
8	Package Type	70(L) x12(W) x8(H) Other - Specify
9	Fiber Length	1 m- 1meter Other - Specify