

Signal Power Combiner

Features



Low insertion loss
High Efficiency
stability and reliability

Application

Wave Fiber Laser
High-Power Laser Equipment
Experimental tests and other areas

Description		Parameter	Unit	Note
Type		SPC-4×1		
Pump Operating Wavelength		1030-1110	nm	
Input Fiber		Nufern-LMA-GDF-20/400-M-0.06/0.46NA	μm	
Output Fiber		Nufern-BD-S100/120/360-STN-0.2NA	μm	
Signal Insertion Loss		-	dB	
Transmission Efficiency		92	%	
Power Handling	Input	1000	W	Each port
	Output	6000	W	
Fiber Type	Input	3mm black armoured cable	-	Every port
	Output	See the QBH Mechanical/Application Parameters	-	
M ²		8	-	
ER		-	dB	
Operating Temperature		-5-+70	℃	
Storage Temperature		-40-+85	℃	
Fiber Length		1.0	m	Input port
		10.0	m	Output port
Dimensions		482x278x44	mm	

Mechanical Dimension



Ordering Information

GCSPC-4×1-1-2-3-4-5-6

1	Signal Operating Wavelength	1064nm Other - Specify
2	Input Fiber	Nufern 20/400 0.06/0.46 DCF Other - Specify
3	Output Fiber	Nufern 100/120/360 0.2NA Other - Specify
4	Power Handling	1500 power
5	Package Type	350x40x33 Other - Specify
6	Fiber Length	1 m- 1meter Other - Specify